

Conforms to WHS Code of Practice

lssued: 08-May-20 Supersedes: 08-Jun-16

FORMULA X-TREME™

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product Name: Formula X-treme High Performance Stripper Product Number: 549

1.2 RELEVENT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST

Product intended for commercial and industrial use only.

Intended Use: Floor finish remover concentrate
Uses Advised Against: Other than per labelled instructions.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Importer:

Eclipse Floor Solutions Pty Ltd

41-43 Steel Street

Capalaba

Queensland 4157

Telephone: (07) 3390 3027

Email: info@eclipsefloorsolutions.com.au Internet: www.eclipsefloorsolutions.com.au

1.4 EMERGENCY TELEPHONE NUMBER

For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident Call: The Australian Poisons Information Hotline All States 24 Hour Ph: 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE MIXTURE

This mixture has been classified as hazardous according to Safe Work Australia criteria.

Acute Toxicity (Oral) - Category 4 Skin Corrosion - Category 1B Eye Damage - Category 1

Acute Toxicity (Inhalation) - Category 4

Specific Target Organ Toxicity (Single Exposure) - Category 3

2.2 LABEL ELEMENTS

Signal Word: Danger

Hazard pictogram(s):



[Corrosion, Exclamation Point]

Hazard Statement(s):

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary Statement(s):*

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.
P312 Call a POISON CENTER/doctor if you feel unwell.

P301+P330+P331+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON

CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.



Conforms to WHS Code of Practice Issued: 08-May-20

Supersedes: 08-Jun-16

Floor Solutions Pty Ltd

FORMULA X-TREMETM
P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

* Precautionary statements listed are as labelled. See Section 16 for additional Precautionary Statements.

2.3 OTHER HAZARDS No other hazards are known to the supplier

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1/3.2 SUBSTANCES/MIXTURES

			Classification		
Ingredient	EC No.	Weight %	CAS No.	Hazard Class	Hazard Statement(s)*
ethylene glycol monobutyl ether	203-905-0	30 - 45	111-76-2	Acute Tox 4 Eye Irrit 2 Skin Irrit 2	H302,H312,H332 H319 H315
benzyl alcohol	202-859-9	20 - 30	100-51-6	Acute Tox 4	H302, H332
ethanolamine	205-483-3	15 - 25	141-43-5	Acute Tox 4 Skin Corr 1B	H302,H312,H332 H314

^{*}See section 16 for the full text of Hazard Statements

SECTION 4: FIRST AID MEASURES

4.1 DECRIPTION OF FIRST AID MEASURES

Eye Contact: Immediately wash out with water for at least 15 minutes. (If easy to do, remove contact lenses, if

worn.) Seek medical attention immediately.

Skin Contact: Immediately wash with plenty of water for at least 15 minutes. (Remove any contaminated clothing

and shoes.) Seek medical attention immediately.

Inhalation: If breathing is difficult: Remove to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center immediately. DO NOT induce vomiting unless directed to do

so by medical personnel. Never give anything by mouth to an unconscious person.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye Contact: Can cause serious eye damage. May cause permanent damage.

Skin Contact: Can cause severe skin burns. May cause permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: May cause burns to mouth, throat and stomach.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

In case of fire: use dry chemical, water spray, foam, carbon dioxide

5.2 SPECIAL HAZARDS ARISING FROM THE MIXTURE

Hazardous combustion products: CO, CO₂

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include but not limited to the above mentioned substances.

5.3 ADVICE FOR FIRE FIGHTERS

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection. Fire-fighters should wear clothing conforming to EN469 for chemical incidents. Materials can splatter above 100°C/212°F. Corrosive material.

HAZCHEM Code: 2X 2 - Fine water spray

X - Liquid tight chemical protective clothing and breathing apparatus. Contain.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Refer to Section 8 for appropriate personal protective equipment.



Conforms to WHS Code of Practice Issued: 08-May-20

08-Jun-16 Supersedes:

FORMULA X-TREME™

15

ENVIRONMENTAL PRECAUTIONS 6.2

Keep spills and cleaning runoff out of sewers and open bodies of water.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP 6.3

Small spills: Absorb spill on inert material (e.g. sand, earth) and dispose of as waste material in accordance with national and regional provisions.

Large spills: Keep spectators away. Floors may be slippery; use care to avoid falling. Neutralize spill area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal.

REFERENCE TO OTHER SECTIONS: Refer to Section 8 & 13 of the SDS.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING 7.1

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only in well-ventilated areas. Avoid breathing vapours or spray mists. Remove and wash contaminated clothing and footwear before reuse.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage temperature (Max. 60°C/140°F) (Min. 1°C/34°F). Keep from freezing. Keep container sealed when not in use. Keep out of reach of children.

SPECIFIC END USE(S): No information available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

Workplace Exposure Limits:

Ingredient	Source	Source TWA (8hours)		STEL (Short term)		Note(s)
ingredient	Source	ppm	mg/m ³	ppm	mg/m ³	140(8)
ethylene glycol monobutyl ether	ACGIH TLV	20	97	-	-	BEI
ethylene glycol monobutyl ether	AU Exposure Standard	20	96.9	50	242	Sk
Ingredient	Source	TWA (8hours)		STEL (SI	STEL (Short term)	
Ingredient	Source	ppm	mg/m³	ppm	mg/m³	Note(s)
ethanolamine	ACGIH TLV	3	7.5	6	15	-
ethanolamine	ALL Ever a server Otalis daniel	2	7.5	0	45	

8.2 **EXPOSURE CONTROLS**

Engineering Controls: Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain

airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness of

7.5

3

ventilation and other control measures.

Environmental exposure controls: No specific environmental exposure controls known.

AU Exposure Standard

Personal Protective Equipment (PPE)

Safety eyewear is recommended to avoid chemical splashes and mists. Eye/Face Protection:

Safety glasses or goggles (EN166).

Hand Protection: Chemical resistant gloves are recommended. (EN374).

Protective index 6, Breakthrough time > 480 mins. (E.g. - nitrile gloves, 0.4 mm thickness) Protective gloves should be selected according to the application and duration of use. Workplace selection should take into consideration handling requirements, physical requirements and exposure

to other substances.

Skin Protection: If major exposure is possible, wear suitable protection such as rubber boots, apron, etc.

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If exposure

limits are exceeded or symptoms are experienced, use an approved respirator with multi-purpose

combination filter. (E.g. - EN 14387- ABEK)



Conforms to WHS Code of Practice

Issued: 08-May-20 Supersedes: 08-Jun-16

FORMULA X-TREME™

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

clear, colorless, liquid Appearance: Odor:

butyl odor

Odor Threshold: No test data available

pH: 11.5 [Method: ASTM E 70]

Melting Point/Freezing Point: No test data available Initial boiling point/boiling range: No test data available

Flash Point: >93°C [Method: Closed cup, ASTM D 56]

Evaporation Rate: No test data available Flammability (solid, gas) Not applicable to liquids Upper/lower flammability/explosive limits: No test data available No test data available Vapor Pressure: Vapor Density: No test data available

Relative Density: 0.98 kg/L @ 20°C [Method: Pycnometer, ASTM D 1475]

Solubility: miscible in water Partition Coefficient (n-octanol/water): No test data available Auto Ignition temperature: No test data available **Decomposition Temperature:** No test data available

Viscosity: < 20 centipoise @ 20°C [Method: Rotational viscometer, Brookfield)

Explosive Properties: none Oxidizing properties: none

9.2 OTHER INFORMATION

> VOC: 60% (as supplied), 2.8% (1:20), 1.9% (1:30), 1.43% (1:40)

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: None known 10.1

CHEMICAL STABILITY: Stable under normal conditions. 10.2

POSSIBILITY OF HAZARDOUS REACTIONS: Product may react strongly with water. Care should be used if diluting; 10.3

product should be slowly added to water.

CONDITIONS TO AVOID: None known

10.5 **INCOMPATIBLE MATERIALS:** Strong acids, bases and oxidizing agents. Do not mix with other chemicals

unless stated on the product label.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS: None known

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY: Toxicity testing has not been completed on the mixture.

Harmful if swallowed. Harmful if inhaled.

ATE _{mix} (oral) - 1463 mg/kg Classified as Acute Toxicity (Oral) - Category 4

ATE mix (dermal) - 2326 mg/kg Based on available data, the classification criteria are not met. ATE _{mix} (inhalation) - 18 mg/l (4 hr/vapour) Classified as Acute Toxicity (Inhalation) - Category 4

Ingredient	CAS#	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC50 Inhalation- (mg/l)
ethylene glycol monobutyl ether	111-76-2	1300	> 2000	guinea pig (1hr), >3.1
benzyl alcohol	100-51-6	1230	2000	rat (8hr), 8.9
ethanolamine	141-43-5	1515	2504	rat (4hr), > 1.3

SKIN CORROSION/IRRITATION: Classified as Skin Corrosive - Category 1B

Causes severe skin burns.

SERIOUS EYE DAMAGE/IRRITATION: Classified as Eye Damage - Category 1

Causes serious eye damage.



Conforms to WHS Code of Practice Issued: 08-May-20

Supersedes: 08-Jun-16

FORMULA X-TREME™

RESPIRATORY OR SKIN SENSITIZATION: Based on available data, the classification criteria are not met.

GERM CELL MUTAGENICITY: Based on available data, the classification criteria are not met.

CARCINOGENICITY: Based on available data, the classification criteria are not met.

REPRODUCTIVE TOXICITY: Based on available data, the classification criteria are not met.

STOT-SINGLE EXPOSURE: Classified as STOT-SE - Category 3

May cause respiratory irritation.

STOT-REPEATED EXPSURE: Based on available data, the classification criteria are not met.

ASPIRATION HAZARD: Based on available data, the classification criteria are not met.

11.2 POTENTIAL ADVERSE HEALTH EFFECTS

Effects and symptoms related to this mixture, if any, are listed in Section 4.2.

SECTION 12: ECOLOGICAL INFORMATION

12.1 TOXICITY: Ecological testing has not been completed on the mixture.

Ingredient	CAS#	LC50 - 96 hr	LC50 - 48 hr	EC50 - 72 hr
ethylene glycol monobutyl ether	111-76-2	vertebrate, 820-1490 mg/ml	Daphnia magna, 835 mg/l	algae, 911 mg/l
benzyl alcohol	100-51-6	vertebrate, 770 mg/ml	Daphnia magna, 400 mg/l	algae, 640 mg/l
ethanolamine	141-43-5	vertebrate, 125-2010 mg/ml	Daphnia magna, 33-93 mg/l	algae, 2.5 mg/l

12.2 PERSISTANCE AND DEGRADABILITY: Testing has not been completed on the mixture.

Ingredient	CAS#	Biodegradation
ethylene glycol monobutyl ether	111-76-2	readily biodegradable
benzyl alcohol	100-51-6	readily biodegradable
ethanolamine	141-43-5	readily biodegradable

12.3 BIOACCUMULATIVE POTENTIAL: Testing has not been completed on the mixture.

Ingredient	CAS#	Partition coefficient n- octanol/water (Log Kow)	Bioconcentration factor (BCF)
ethylene glycol monobutyl ether	111-76-2	0.81	< 100
benzyl alcohol	100-51-6	not available	<100
ethanolamine	141-43-5	-1.91	< 100

12.4 MOBILITY IN SOIL: Testing has not been completed on the mixture.

Ingredient	CAS#	Soil Organic Carbon- Water Partitioning Coefficient (Koc)
ethylene glycol monobutyl ether	111-76-2	67
benzyl alcohol	100-51-6	not available
ethanolamine	141-43-5	1.17

12.5 OTHER ADVERSE EFFECTS: None known

12.6 ADDITIONAL INORMATION: Based on available data, the classification criteria are not met.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, regional and national regulations.

During disposal activities, refer to Section 8 for relevant exposure controls and PPE requirements.



FORMULA X-TREME™

Conforms to WHS Code of Practice

lssued: 08-May-20 Supersedes: 08-Jun-16

Supersedes: 08-Jun-16

SECTION 14: TRANSPORT INFORMATION

This mixture has been classified as a dangerous good in accordance with ADG regulations.

14.1 UN NUMBER: UN1760

14.2 UN PROPER SHIPPING NAME: Corrosive liquid, n.o.s. (ethanolamine)

14.3 TRANSPORT HAZARD CLASSES: 8
14.4 PACKING GROUP: II
14.5 ENVIRONMENTAL HAZARDS: N/A
14.6 SPECIAL PRECAUTIONS FOR USER:

Package volumes < 1 L are shipped as Limited Quantity; as permitted by hazard class and quantity limits.

HAZCHEM CODE: 2X

IMDG

Emergency Schedules (EmS): Fire F-A, Spillage S-B

Stowage and Segregation: Category B. Clear of living quarters.

Marine Pollutant: None

ADR/RID

Class: 8
Item Number: 80
Classification Code C9

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MAPROL73/78 AND THE IBC CODE: N/A

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE MIXTURE

AICS STATUS: Ingredients are listed on AICS inventory or are exempt.

POISON SCHEDULE:

(SUSMP)

Ingredient	%	Schedule
ethylene glycol monobutyl ether	> 10	6
ethanolamine	> 5	6

SECTION 16: OTHER INFORMATION

REVISION INFORMATION:

08-May-20 - Revision § 9

ABBREVIATIONS:

N/A - Not applicable N/E - Not Established

N/L - Not Listed

ACGIH - American Conference of Governmental Industrial Hygienists

TLV - Threshold Limit Value

AICS - Australian Inventory of Chemical Substance

SUSMP - Standard for the Uniform Scheduling of Medicines and Poisons

FULL TEXT OF HAZARD STATEMENTS:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.



Conforms to WHS Code of Practice

lssued: 08-May-20 Supersedes: 08-Jun-16

FORMULA X-TREME™

FULL TEXT OF PRECAUTIONARY STATEMENTS:

P261 Avoid breathing mist/vapours/spray. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P321 Specific treatment (see ... on this label).

P337+313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+233 Store in well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

ISSUED BY:

Chemical/R&D Department

Amano Pioneer Eclipse Corporation